

OVERVIEW

- ♦ The LA618 is a modern sleek linear luminaire that provides a soft, shadow free illumination.

FEATURES

- ♦ Available in 2ft. / 4ft. / 5ft. / 8ft. nominal lengths.
- ♦ CRI greater than 80.
- ♦ Rated Life [L70] — 50,000 Hours.
- ♦ Fixture lumens per watt ratios [LpW] — Greater than 104.
- ♦ 120-277V (50/60Hz)
- ♦ 0-10V Dimming.

HOUSING

- ♦ Extrusion aluminum material with screw-less end caps.

LENS

- ♦ Polycarbonate lens provides a soft, evenly diffused light.

PROJECT _____

TYPE _____

QTY. _____

APPLICATIONS

- ♦ Lobbies
- ♦ Conference Rooms
- ♦ Showrooms
- ♦ Libraries
- ♦ Offices

INSTALLATIONS

- ♦ Designed for pendant mount with adjustable aircraft cable. Sliding brackets are provided for easy installation.
- ♦ Cable suspends 48" from ceiling. Other lengths available.
- ♦ Available as individual units.
- ♦ Suitable for ceiling surface mount applications.

LED

- ♦ Custom designed LED system with unique optics ensures perfectly even illumination.
- ♦ Dimming down to 10% on 0-10V dimming controls is standard.

WARRANTY

- ♦ 5 year limited warranty is standard.
- Exclusions may apply. Contact factory for terms and conditions.*

ORDERING GUIDE

Fill in the boxes below with the corresponding **bold** options.

Example: **LA618-4-37L-40K-U-D2**

LA618				U	D2		
SERIES	FIXTURE LENGTH	NOMINAL LUMENS	COLOR TEMP.	VOLTAGE	DIMMING	FINISH	OPTIONS
LA618	2 2FT. 4 4FT. 5 5FT. 8 8FT.	2FT. 18L 1800 4FT. 37L 3700 5FT. 45L 4500 8FT. 68L 6800	30K 3000K 35K 3500K 40K 4000K 45K 4500K 50K 5000K	U 120-277V	D2 0-10V Dimming to 10%*	WH White BK Black GR Grey	Mounting SM Ceiling Surface Mount

*Compatible with 0-10V dimmers.

2FT. LUMEN PACKAGE					
Nominal Lumens	Color Temp.	Power (W)	Delivered Lumens	LpW	DLC
1800	3000K	17W	1777	105	✓
	4000K	17W	1834	109	✓
	5000K	17W	1906	111	✓

4FT. LUMEN PACKAGE					
Nominal Lumens	Color Temp.	Power (W)	Delivered Lumens	LpW	DLC
3700	3000K	34W	3535	104	✓
	4000K	35W	3728	107	✓
	5000K	35W	3831	111	✓

5FT. LUMEN PACKAGE					
Nominal Lumens	Color Temp.	Power (W)	Delivered Lumens	LpW	DLC
4500	3000K	41W	4359	106	✓
	4000K	42W	4575	108	✓
	5000K	43W	4685	110	✓


8FT. LUMEN PACKAGE					
Nominal Lumens	Color Temp.	Power (W)	Delivered Lumens	LpW	DLC
6800	3000K	61W	6475	105	✓
	3500K	61W	6677	109	✓
	4000K	61W	6878	112	✓
	4500K	61W	7078	115	✓
	5000K	61W	7281	119	✓

PHOTOMETRICS

Photometric reports are available at www.ullighting.net

DIMENSIONS

END VIEW



FIXTURE SIZE			
Nominal Size	Length (L)	Width (W)	Height (H)
2FT.	23.86	1.97	3.15
4FT.	47.40	1.97	3.15
5FT.	59.21	1.97	3.15
8FT.	94.50	1.97	3.15